



EnForcer® GSE™ Charger
400hz - 3 Phase - 20kw - 200 amp output

The Perfect Charge Every Time

The EnForcer® GSE™ charger uses an intelligent microprocessor to control charge current and voltage during the charge cycle. This precise control allows the EnForcer GSE to charge a variety of battery technologies and charge in a wide range of temperature environments. The charger includes a programmable charge profile that includes fast and opportunity charge for demanding GSE applications.

EnForcer GSE 400hz Specifications

Input Power	3 Phase 400hz
Input Voltage	200 VAC
Output Voltage	24-80V
Maximum Output Power	20 kw
Maximum Output Current (80v)	192a
Recharge Range (80v)	250AH - 1000AH
Enclosure	Nema 3R pending
Operating Temperature	-40°C to 50°C
Certifications	UL and CE pending
Dimensions (In.)	15.86W x 41.71D x 15.7H
Weight	310 lbs
Warranty	3 Years

EnForcer® GSE™ Charger



Part Numbers:
GSE-30-800G
GSE-40-800G

Other features include:

- Uses existing 400hz power supplies and cable connections
- No additional electrical infrastructure
- Outdoor enclosure
- Small size allows for "on-board" mounting
- Fast charge, opportunity charge, or conventional charge
- Completely programmable to application
- Automatic equalize charging
- Data logging for monitoring and maintenance
- Global service network from the world's dominant battery and charger manufacturer



1-800-enersys

www.enersysmp.com